Anthem MCA 225 Gen 2

Eindversterkers



Technische specificaties

Merk	Anthem
Model	MCA 225 Gen 2
Productcategorie	Eindversterkers
Frequentiebereik	8Ω = 20 Hz - 20 kHz ± 0.1 dB 4Ω = 20 Hz - 20 kHz ± 0.1 dB 2Ω = 20 Hz - 20 kHz ± 0.2 dB
Ingangen	Single-Ended, Balanced, Relay Trigger (3.5-mm Mono Jack)
Uitgangen	Speaker Binding Posts, Relay Trigger (3.5-mm Mono Jack)
Kanalen	2
Ingangsgevoeligheid	1.5 Vrms (225 W into 8 Ω)
Ingangsimpedantie	10kΩ (RCA), 15kΩ (XLR)
Slew rate	30 V/µs
Kanaalscheiding	n/a
Overspraak	n/a

Technische specificaties

Signaal-ruisverhouding	120 dB (IEC-A, ref. 225 W)
Totale harmonische vervorming plus ruis	0.0010% (1 kHz), 0.002% (20 kHz) @ 100 W
Intermodulatievervorming	ITU-R (19 kHz + 20 kHz) 0.0005% @ 100 W SMPTE (60 Hz + 7 kHz) 0.002% @ 100 W
Dempingsfactor	(20 Hz - 1 kHz) 300
Display voorzijde	LED Status Indicator
Constructie	Anodized Aluminum Faceplate with Steel Chasis
Afmetingen (D) (excluding Power Cord)	18-1/8" (46 cm)
Afmetingen (W)	17" (43.18 cm)
Afmetingen (H) (with feet)	6-5/8" (16.9 cm)
Hoogte met rackmontage	4U
Verbruik zonder signaal	35 W
Uitvoering 120 V	In countries where the line voltage is 120 V, this product operates from a single phase AC power source that supplies between 108 V and 132 V at a frequency of 60 Hz.
Uitvoering 220-240 V	In countries where the line voltage is 220, 230, or 240 V, this product operates from a single phase AC power source that supplies between 198 V and 264 V at a frequency of 50 Hz.
Gewicht	40 lb (18 kg)