Fyne Audio F704SP

Luidsprekers



Technische specificaties

Merk	Fyne Audio
Model	F704SP
Productcategorie	Luidsprekers
Systeemtype	2 ½ way, downwards firing port, met BassTrax™ Tractrix diffuser, twin cavity loading system
Nominale impedantie	8 Ohm
Luidsprekerbezetting	1 x 300mm IsoFlare, point source driver, multi-fibre bass / midrange cone, FyneFlute surround with 75mm titanium dome compression tweeter, neodymium magnet system. 1 x 300mm multi-fibre bass FyneFlute surround.
Afmetingen (H × B × D)	1353 x 579 x 568mm (53.3 x 22.8 x 22.4")
Aanbevolen versterkervermogen (W RMS)	30 - 300
Continue belastbaarheid (W RMS)	150

Technische specificaties

Gevoeligheid (2,83 V / 1 m)	96dB
Frequentiebereik (-6 dB, in de ruimte)	22Hz - 26kHz
Scheidingsfrequentie	250Hz & 850Hz
Type wisselfilter	Bi-wired passive low loss, 2nd order low pass, 1st order high pass. Cryogenically treated
Kastconstructie	Pressed high density birch ply with extensive internal bracing.
S-Trax-positie vanaf voorrand kast	119mm (4.7")
SuperTrax-positie vanaf voorrand kast	95mm (3.7")
Nettogewicht per stuk	71.5kg (157.6lbs)
Afwerkingen	Natural Walnoot / Piano Gloss Walnoot / Piano Gloss Zwart / Piano Gloss Wit