MartinLogan ElectroMotion ESL X

Vloerstaande luidsprekers



Technische specificaties

Merk	MartinLogan
Model	ElectroMotion ESL X
Productcategorie	Vloerstaande luidsprekers
Frequentiebereik	41-22,000 Hz ±3dB
Impedantie	6 Ω, 1.6 @ 20kHz Compatible with 4, 6, or 8 Ohm rated amplifiers.
Gevoeligheid	91 dB/2.83 volts/meter
Luidsprekerbezetting	Custom-wound audio transformer, air core coils, large steel laminate inductors, polyester capacitors, en low DF electrolytic capacitors
Ingangen	Custom 5-way bi-wire tool-less binding posts
Aanbevolen versterkervermogen	20-400 W per kanaal
Horizontale afstraling	30°

Technische specificaties

Verticale afstraling	40" (101.6cm) line source
Scheidingsfrequentie	400Hz
Hogetonenunit	XStat™ CLS™ electrostaic transducer » Panel Dimensions: 40" x 8.6" (102 x 22cm) » Radiating Area: 344 in² (2,244 cm²)
Lagetonenunit	Twee 8” (20.3 cm) high excursion, high-rigidity paper cones with extended throw driver assembly, non-resonance asymmetrical chamber format, bass reflex.
Afmetingen	59.2" x 9.4" x 20.7 " (150.3cm x 23.8cm x 52.6cm)
Gewicht	52 lbs. (23.6 kg)