MartinLogan ElectroMotion ESL

Vloerstaande luidsprekers



Technische specificaties

Merk	MartinLogan
Model	ElectroMotion ESL
Productcategorie	Vloerstaande luidsprekers
Frequentiebereik	42-22,000 Hz ±3dB
Impedantie	6 Ω, 1.6 @ 20kHz Compatible with 4, 6, or 8 Ohm rated amplifiers.
Gevoeligheid	91 dB/2.83 volts/meter
Luidsprekerbezetting	Custom-wound audio transformer, air core coils, large steel laminate inductors, polyester capacitors, en low DF electrolytic capacitors
Ingangen	Push style with banana jacks
Aanbevolen versterkervermogen	20-300 W per kanaal
Horizontale afstraling	30°

Technische specificaties

Verticale afstraling	34" (71cm) line source
Scheidingsfrequentie	500Hz
Hogetonenunit	XStat™ CLS™ electrostaic transducer » Panel Dimensions: 34" x 8.6" (86 x 22cm) » Radiating Area: 292 in² (1,892 cm²)
Lagetonenunit	8" (20.3cm) high excursion, high-rigidity paper cone with extended throw drive assembly, non-resonance asymmetrical chamber format; bass reflex
Afmetingen	52.1" x 9" x 16.3 " (132.3cm x 22.9cm x 41.4cm)
Gewicht	35.5 lbs. (16.1 kg)