MartinLogan Grotto 12

Subwoofers



Technische specificaties

Merk	MartinLogan
Model	Grotto 12
Productcategorie	Subwoofers
Frequentiebereik	22-120 Hz ±3 dB (Anechoic via LFE input)
Ingangen	Line Level: Left, Right, en LFEXLR: LFE Speaker Level: Left and Right (requires banana plugs)
Uitgangen	RCA Sub Out (combines and repeats all incoming signals to an additional subwoofer)
Stroomverbruik	Max: 1000W Standby (Wireless Disabled): 0.5W Standby (Wireless Enabled): <2W *Transmitter and Subwoofer combined
Afmetingen (H × B × D)	17.8" x 17.9" x 17.9" (45.2cm x 45.4cm x 45.4cm)
Digitale signaalverwerking	Ultra High-Resolution 500MHz Vojtko DSP Engine with 64bit processing

Technische specificaties

Lagetonenunit	Triple 12" (25.4cm) Hybrid Woofer System consisting of 1x high-excursion, aluminum cone in a cast aluminum basket with 2x aluminum cone passive radiators for enhanced low frequency output.
Behuizing	Sealed 1" thick MDF cabinet with center brace and reinforced MDF woofer baffles
Versterker	MartinLogan Magnitude MT2kW Amplifier: 2000W peak (1000W continuous)
Bediening achterpaneel	Level: Interactive LED Backlit Knob, Min-Max Tone Sweep: Sweep Start and Pause (with status light) Power Mode: On, 12v Trigger, Auto Wireless Audio Pairing Button (for included MartinLogan wireless transmitter)
Bediening via Bluetooth	Level: -40 to 12dB (Min-Max) Low-Pass Filter (Frequency): 35-120Hz (1° Increments) Low-Pass Filter (Order): Bypass, Third, Vierth Phase: 0-180° (1° Increments) Phase (Polarity): Normal, Inverted Preset Listening Modes: Movie, Music, Night 20-30Hz Level: ±10dB Anthem Room Correction (ARC Genesis): On, Off Tone Sweep (120-20Hz): On, Off, Pause (Frequency)
Draadloze ingangen	Integrated Wireless Receiver, Wireless Transmitter Included
Voeten	Integrated Anti-Vibration Feet (carpet spikes included)
Gewicht	82.5 lbs (37.4 kg)
Afwerking	Gloss Zwart