MartinLogan Illusion ESL C34A

Centerluidsprekers



Technische specificaties

Merk	MartinLogan
Model	Illusion ESL C34A
Productcategorie	Centerluidsprekers
Frequentiebereik	45-23,000 Hz ±3dB
Impedantie	6 Ω Compatible with 4, 6, or 8 Ohm rated amplifiers.
Gevoeligheid	90 dB/2.83 volts/meter
Luidsprekerbezetting	Custom-wound audio transformer, air core coils, polypro- pylene capacitors. 24-bit DSP based preamplifier (used with woofer amplifier).
Ingangen	AC Power, RJ45 (for ARC), mini USB (for ARC)
Stroomverbruik	Max: 300W per kanaal Standby: <1W per kanaal
Aanbevolen versterkervermogen	20-600 W per kanaal
Horizontale afstraling	30°

Technische specificaties

Scheidingsfrequentie	500, 2000 Hz
Hogetonenunit	Twee 1.25" x 2.4" (3.2cm x 6.1cm) Folded Motion XT Transducers with 4.5" x 2.75" (11.4cm x 7cm) diaphragm.
Lagetonenunit	Vier 6.5" (16.5cm) cast basket, high excursion, rigid aluminum cone with extended throw drive assembly, non-resonance asymmetrical chamber format.
Versterker	1x 250 W/channel (4 Ω), 500 W peak
Ruimtecorrectie (Bass Section)	Anthem Room Correction (ARC) Ready (Sold Separately)
Audioregelingen	Bass: ±10dB under 75Hz Mid-Bass: -2dB, 0dB, +2dB ARC Room EQ: On, Off
Afmetingen	23.75" x 32.35" x 23.1 " (60.3cm x 82.2cm x 58.6cm)
Gewicht	90 lbs. (40.9 kg)