MartinLogan Motion 6i

Luidsprekers



Technische specificaties

Merk	MartinLogan
Model	Motion 6i
Productcategorie	Luidsprekers
Frequentiebereik	120-23,000 Hz ±3dB
Impedantie	6 Ω Compatible with 4, 6, or 8 Ohm rated amplifiers.
Gevoeligheid	89 dB/2.83 volts/meter
Luidsprekerbezetting	Custom air core coil and low DCR steel laminate inductors. Polyester film capacitors in series and low DF electrolytic capacitors in parallel. Overall system thermal/current protection.
Ingangen	Push style with banana jacks
Aanbevolen versterkervermogen	20-130 W per kanaal
Horizontale afstraling	80°
Verticale afstraling	80°

Technische specificaties

Scheidingsfrequentie	4,000 Hz
Hogetonenunit	0.94" × 1" (2.4cm × 2.5cm) Folded Motion Transducer with 2.8" × 1.25" (13.3cm × 4.4cm) diaphragm
Lagetonenunit	Twee 3.5" (8.9cm) poly cone with stamped steel basket. Non-resonant asymmetrical chamber format. Rigid structured dust cap to reduce cone break-up modes. Sealed.
Afmetingen	5.2" x 17.5" x 4 " (13.2cm x 44.4cm x 10.1cm)
Gewicht	5.7 lbs. (2.58 kg)