MartinLogan Motion SLM

Luidsprekers



Technische specificaties

Merk	MartinLogan
Model	Motion SLM
Productcategorie	Luidsprekers
Frequentiebereik	110-25,000 Hz ±3dB
Impedantie	4 Ω Compatible with 4, 6, or 8 Ohm rated amplifiers.
Gevoeligheid	94 dB/2.83 volts/meter
Luidsprekerbezetting	Custom air core coil inductors. Polyester film capacitors in series and low DF electrolytic capacitors in parallel. Overall system thermal/cur- rent protection.
Ingangen	Low-profile push style
Aanbevolen versterkervermogen	20-140 W per kanaal
Horizontale afstraling	80°
Verticale afstraling	80°

Technische specificaties

Scheidingsfrequentie	2,600 Hz
Hogetonenunit	1" × 1.4" (2.6cm × 3.6cm) Folded Motion Transducer with 5.25" × 1.75" (13.3cm × 4.4cm) diaphragm
Lagetonenunit	Twee 4” (10.2cm) paper cone. Twee 4” (10.2cm) paper cone passive radiators.
Afmetingen	25.3" x 6.4" x 1.83 " (64.2cm x 16.2cm x 4.75cm)
Gewicht	6.5 lbs. (3 kg)