MartinLogan Statement 40XW

Inbouwluidsprekers



Technische specificaties

Merk	MartinLogan
Model	Statement 40XW
Productcategorie	Inbouwluidsprekers
Frequentiebereik	48-25,000 Hz ± 3 dB
Impedantie	4 Ω. Compatible with 4, 6, or 8 ohm rated amps.
Gevoeligheid	95 dB @ 2.83 volts/ meter
Luidsprekerbezetting	Custom air core coil inductors, polypropylene film capacitors, en low DF electrolytic capacitors.
Afstraling tweeter (horizontaal × verticaal)	80° x 52-inch line source
Scheidingsfrequentie	300, 2700 Hz
Hogetonenunit	Sixteen 1.25 x 2.4 inch (3.2 x 6.1 cm) Folded Motion XT Obsidian transducer with 4.5 x 2.75 inch (11.4 x 7 cm) diaphragm.

Technische specificaties

Middentonenunits	Sixteen 3.5-inch (8.9 cm) black unidirectional carbon fiber multi-section cone with Nomex® backer and cast aluminum basket, sealed back chamber format. Concave dust cap.
Lagetonenunit	Eight 6.5-inch (16.5 cm) black unidirectional carbon fiber multi-section cone with Nomex® backer and cast aluminum basket, sealed back chamber format. Concave dust cap.
Aanbevolen versterkervermogen	50-800 W
Maximale belastbaarheid	400 W
Luidsprekerterminals	Push style (two sets for easy installation)
Luidsprekerrooster (height x width)	11.5 x 59.5 inch (292 x 1511 mm)
Gewicht	150 lb (68.1 kg)