Naim Audio NAC 332

Voorversterkers



Technische specificaties

Merk	Naim Audio
Model	NAC 332
Productcategorie	Voorversterkers
Analoge ingangen	1 x 8-pin DIN (47kΩ, 2.2V typical, 9.5Vrms Max) 2 x 5-pin DIN (47kΩ, 2.2V typical, 9.5Vrms Max) 3 x RCA pair (47kΩ, 2.2V typical, 9.5Vrms Max) 2 x XLR gebalanceerd pair (100kΩ, 2.2V typical, 9.5V max) 8-pin DIN compatible with 5-pin DIN 8-pin DIN has +/-18V (for compatible external phono stages e.g. NVC TT)
Analoge uitgangen	1 x XLR pair (gebalanceerd 10Vrms max) 1 x RCA pair (10Vrms max) 1 x 6.35mm headphone jack (1.5W into 16Ω)
Bediening	Eight buttons for quick access to standby, mute and inputs. Volume control.
Overspraak - Line	Line: 90dB at 1kHz, volume at 0dB (Line: 70dB at 20kHz, volume at 0dB)
Frequentiebereik - line	Line: 3Hz to 40kHz -3dB

Technische specificaties

Vervorming - Line	Line: 0.003% @2.2V input volume at 0dB, 1kHz (Line: 0.018% @2.2V input volume at 0dB, 20kHz). Dominated by 2nd harmonic and noise
Analoge versterkingsfactor	Preamplifier at max volume: 15.5dB
Hoofdtelefoonuitgangen	1 x jack 6,35 mm
USB-poorten	1 x USB port (for updates)
Bediening via app	Focal & Naim App
Bedieningssysteem	Zigbee RF bi-directive remote control
Automatische stand-by	<20 min.
Stroomverbruik, uitgeschakeld	< 0.3W
Stroomverbruik in stand-by	< 0.5W
Stroomverbruik in netwerkstand-by	< 2W
Stroomverbruik bij gebruik	20 W
Netsnoer	PowerLine Lite
Netvoeding	100V, 115V or 230V, 50/60Hz
Optionele voedingen	NPX 300
Breedte	43.2 cm / 17 in
Hoogte	9.15 cm / 3.62 in
Diepte	31.75 cm / 12.5 in
Gewicht	11 kg / 24.25 lb