Paradigm Loudspeakers CI Pro P1 LCR v2

Inbouwluidsprekers



Technische specificaties

Merk	Paradigm Loudspeakers
Model	CI Pro P1 LCR v2
Productcategorie	Inbouwluidsprekers
Ontwerp	3-driver, 2-way, shallow enclosure in-wall design, Advanced SHOCK- MOUNT™ System
Impedantie	Compatible with 8 Ω
Wisselfilter	2nd-order electro-acoustic at 2.2 kHz
Frequentierespons op de as	±3 dB from 94 Hz - 22 kHz
Frequentierespons 30° buiten de as	±3 dB from 94 Hz - 19 kHz
Hogetonenunit	1” (2.5cm) Aluminum Magnesium Ceramic (AL-MAC™) Tweeter with Exclusive Perforated Phase-Aligning (PPA™) Tweeter Lens and Reduced Edge Diffraction (RED™) Technology

Technische specificaties

Midden-/lagetonenunit	Twee 5.5” (13.9cm) CARBON-X™ Cone with overmolded Active Ridge Technology (ART™) surround, Advanced SHOCK-MOUNT™ System, FEA-Optimized Ultra Rigid Cast-Aluminium Baskets
Gevoeligheid (ruimte / anechoïsch)	92 dB / 89 dB
Onderste grensfrequentie	74 Hz
Aanbevolen versterkervermogen	15-120 W
Maximaal ingangsvermogen	90 W
Afmetingen inbouwopening	19-5/8” x 6-5/8” (49.8cm x 16.8cm)
Minimale inbouwdiepte achter ½-inch wandplaat	3-7/8” (9.8cm)
Afmetingen (H × B × D) (INCLUDES GRILLE).	20-5/8” x 7-5/8” x 4-1/8” (52.4cm x 19.4cm x 10.5cm)
Gewicht	15.0 lbs (6.8 kg)
Afwerkingen	Wit, paintable grille, black speaker