Paradigm Loudspeakers CI Pro P5 LCR v2

Inbouwluidsprekers



Technische specificaties

Merk	Paradigm Loudspeakers
Model	CI Pro P5 LCR v2
Productcategorie	Inbouwluidsprekers
Ontwerp	4-driver, dual passive radiators, 3-way, shallow enclosure in-wall design, Advanced SHOCK-MOUNT™ System
Impedantie	Compatible with 8 Ω
Wisselfilter	3rd-order electro-acoustic at 2.8 kHz, 2nd-order electro-acoustic @ 500 Hz
Frequentierespons op de as	±3 dB from 84 Hz - 22 kHz
Frequentierespons 30° buiten de as	±3 dB from 84 Hz - 19 kHz
Hogetonenunit	1” (2.5cm) Aluminum Magnesium Ceramic (AL-MAC™) Tweeter with Exclusive Perforated Phase-Aligning (PPA™) Tweeter Lens and Reduced Edge Diffraction (RED™) Technology

Technische specificaties

Middentonenunit	6.5” (16.5cm) Coaxial AL-MAG™ Cone with SHOCK-MOUNT™ Isolation Mounting System, a 1” high-temp multi-layered voice coil with Apical™ former
Lagetonenunit	Twee 6.5” (16.5cm) CARBON-X™ Cone with overmolded Active Ridge Technology (ART™) surround, Advanced SHOCK-MOUNT™ System, FEA-Optimized Ultra Rigid Cast-Aluminium Baskets
Passieve radiatoren	Twee 6.5” (16.5cm) CARBON-X™ Cone with overmolded Active Ridge Technology (ART™) surround, Advanced SHOCK-MOUNT™ System, FEA-Optimized Ultra Rigid Cast-Aluminium Baskets
Gevoeligheid (ruimte / anechoïsch)	94 dB / 91 dB
Onderste grensfrequentie	65 Hz
Aanbevolen versterkervermogen	15- 200 W
Maximaal ingangsvermogen	130 W
Afmetingen inbouwopening	42” x 8-1/2” (106.6cm x 21.6cm)
Minimale inbouwdiepte achter ½-inch wandplaat	3-7/8” (9.8cm)
Gewicht	29.0 lbs (13.2 kg)
Afwerkingen	Wit, paintable grille, black speaker