Paradigm Loudspeakers CI Pro P65-RX v2

Inbouwluidsprekers



Technische specificaties

Merk	Paradigm Loudspeakers
Model	CI Pro P65-RX v2
Productcategorie	Inbouwluidsprekers
Ontwerp	2-driver, 2-way in-ceiling, Advanced SHOCK-MOUNT™ System, Nylon Reinforced Baffle
Impedantie	Compatible with 8 Ω
Wisselfilter	2nd-order electro- acoustic at 2.5 kHz
Frequentierespons op de as	±3 dB from 75 Hz - 22 kHz
Frequentierespons 30° buiten de as	±3 dB from 75 Hz - 18 kHz
Hogetonenunit	1” (2.5cm) Aluminum Magnesium Ceramic (AL-MAC™) Tweeter with Exclusive Perforated Phase-Aligning (PPA™) Tweeter Lens and Reduced Edge Diffraction (RED™) Technology

Technische specificaties

Midden-/lagetonenunit	6.5” (16.5cm) CARBON-X™ Cone with overmolded Active Ridge Technology (ART™) surround, Advanced Shock-Mount™ System, FEA-Optimized Ultra Rigid Cast- Aluminium Baskets
Gevoeligheid (ruimte / anechoïsch)	91.5 dB / 87.5 dB
Onderste grensfrequentie	41 Hz
Aanbevolen versterkervermogen	15-100 W
Maximaal ingangsvermogen	80 W
Afmetingen inbouwopening	7-3/4” (19.7cm) dia.
Minimale inbouwdiepte achter ½-inch wandplaat	3-5/8” (9.2cm)
Afmetingen (H × B × D) (INCLUDES GRILLE).	8-7/8” (diameter) x 4-1/4” (depth) (22.6cm x 10.7cm)
Gewicht	5.7 lbs (2.6 kg)
Afwerkingen	Wit, paintable grille, black speaker