Paradigm Loudspeakers CI Pro P80-IW v2

Inbouwluidsprekers



Technische specificaties

Merk	Paradigm Loudspeakers
Model	CI Pro P80-IW v2
Productcategorie	Inbouwluidsprekers
Ontwerp	2-driver, 2-way in-wall, Advanced SHOCK-MOUNT™ System, Die-Cast Aluminum Baffle
Impedantie	Compatible with 8 Ω
Wisselfilter	2nd-order electro- acoustic at 2.5 kHz
Frequentierespons op de as	±3 dB from 55 Hz - 22 kHz
Frequentierespons 30° buiten de as	±3 dB from 55 Hz - 18 kHz
Hogetonenunit	1” (2.5cm) Aluminum Magnesium Ceramic (AL-MAC™) Tweeter with Exclusive Perforated Phase-Aligning (PPA™) Tweeter Lens and Reduced Edge Diffraction (RED™) Technology

Technische specificaties

Midden-/lagetonenunit	8” (20.3cm) CARBON-X™ Cone with overmolded Active Ridge Technology (ART™) surround, Advanced Shock-Mount™ System, FEA-Optimized Ultra Rigid Cast- Aluminium Baskets
Gevoeligheid (ruimte / anechoïsch)	91.5 dB / 87.5 dB
Onderste grensfrequentie	30 Hz
Aanbevolen versterkervermogen	15-150 W
Maximaal ingangsvermogen	100 W
Afmetingen inbouwopening	11-9/16” x 8-1/16” (29.3cm x 20.5cm)
Minimale inbouwdiepte achter ½-inch wandplaat	3-3/8” (8.6cm)
Afmetingen (H × B × D) (INCLUDES GRILLE).	12-5/8” x 9-1/4” x 4” (32.1cm x 23.4cm x 10.2cm)”
Gewicht	8.6 lbs (3.9 kg)
Afwerkingen	Wit, paintable grille, black speaker