Paradigm Loudspeakers CI Pro P80-R v2

Inbouwluidsprekers



Technische specificaties

Merk	Paradigm Loudspeakers
Model	CI Pro P80-R v2
Productcategorie	Inbouwluidsprekers
Ontwerp	2-driver, 2-way in-ceiling, Advanced SHOCK-MOUNT™ System, Nylon Reinforced Baffle
Impedantie	Compatible with 8 Ω
Wisselfilter	2nd-order electro- acoustic at 2.5 kHz
Frequentierespons op de as	±3 dB from 64 Hz - 22 kHz
Frequentierespons 30° buiten de as	±3 dB from 64 Hz - 18 kHz
Hogetonenunit	1” (2.5cm) Aluminum Magnesium Ceramic (AL-MAC™) Tweeter with Exclusive Perforated Phase-Aligning (PPA™) Tweeter Lens and Reduced Edge Diffraction (RED™) Technology

Technische specificaties

Midden-/lagetonenunit	8” (20.3cm) CARBON-X™ Cone with overmolded Active Ridge Technology (ART™) surround, Advanced Shock-Mount™ System, FEA-Optimized Ultra Rigid Cast- Aluminium Baskets
Gevoeligheid (ruimte / anechoïsch)	92 dB / 88 dB
Onderste grensfrequentie	39 Hz
Aanbevolen versterkervermogen	15-110 W
Maximaal ingangsvermogen	80 W
Afmetingen inbouwopening	9-3/16” (23.4cm) dia.
Minimale inbouwdiepte achter ½-inch wandplaat	3-7/8” (9.8cm)
Afmetingen (H × B × D) (INCLUDES GRILLE).	10-1/4” (diameter) x 4-1/2” (depth) (26.1cm x 11.4cm)
Gewicht	6.4 lbs (2.9 kg)
Afwerkingen	Wit, paintable grille, black speaker