Paradigm Loudspeakers Founder 70LCR

Centerluidsprekers



Technische specificaties

Merk	Paradigm Loudspeakers
Model	Founder 70LCR
Productcategorie	Centerluidsprekers
Ontwerp	4-driver, 3 way LCR, sealed enclosure
Impedantie	Compatible with 8 Ω
Afmetingen (H × B × D)	8” x 18.9” x 12.3” (20.4cm x 48cm x 31.3cm)
Wisselfilter	2nd order electro-acoustic at 2.2 kHz (tweeter), 2nd order @ 700 Hz (bass)
Frequentierespons op de as	±2dB from 79 Hz - 23 kHz
Frequentierespons 30° buiten de as	±2dB from 79 Hz - 17 kHz

Technische specificaties

Hogetonenunit	Coaxial 1" (25mm) AL-MAC™ Ceramic Dome with Oblate Spheroid Waveguide (OSW™) en Perforated Phase-Aligning (PPA™) Tweeter Lens, ferro-fluid damped / cooled, Patent Pending Dual Gap Motor Structure
Middentonenunit	Coaxial 6” (152mm) AL-MAG™ Cone with SHOCK-MOUNT™ Isolation Mounting System, a 2” high-temp multi-layered voice coil with Apical™ former, Patented Dual-Sync™ Continuous Flux Motor
Lagetonenunit	Twee 5.5" (127mm Ultra-HighExcursion CARBON-X™ Unibody Cone, Gen3 Active Ridge Technology (ART™), en a 1.5” high-temp multi-layered voice coil with ventilated Apical™ former
Gevoeligheid (ruimte / anechoïsch)	92 dB / 89 dB
Onderste grensfrequentie	47 Hz (DIN)
Aanbevolen versterkervermogen	15 - 220 W
Maximaal ingangsvermogen	150 W
Gewicht	30 lbs (13.6 kg) each
Afwerkingen	Piano Zwart, Zwart Walnoot, Midnight Cherry, Walnoot