Paradigm Loudspeakers GO4

Buitenluidsprekers



Technische specificaties

Merk	Paradigm Loudspeakers
Model	GO4
Productcategorie	Buitenluidsprekers
Ontwerp	2-driver, 2-way acoustic suspension, weather, water, UV-resistant PolyGlass™ enclosure
Impedantie	Compatible with 8 Ω
Wisselfilter	2nd-order electro-acoustic at 2.5 kHz
Frequentierespons op de as	±3 dB from 135 Hz - 20 kHz
Hogetonenunit	3/4" (1.9cm) X-PAL™ dome, ferro-fluid damped / cooled, Reduced Edge Diffraction (RED™) Technology, die-cast low diffraction baffle/heat sink
Midden-/lagetonenunit	4" (10 cm) mineral-filled polypropylene cone, Nitrile-Butadiene Rubber (NBR) surround
Gevoeligheid (ruimte / anechoïsch)	87 dB / 83 dB

Technische specificaties

Onderste grensfrequentie	80 Hz
Aanbevolen versterkervermogen	15 - 120 W
Maximaal ingangsvermogen	60 W
Afmetingen (DIAMETER X DEPTH)	5-1/4” (diameter) x 8” (depth) 13.4cm x 20.3cm
Gewicht	4.3 lbs. (2.6 kg)
Afwerkingen	Satin Bronze