Paradigm Loudspeakers GO6

Buitenluidsprekers



Technische specificaties

Merk	Paradigm Loudspeakers
Model	GO6
Productcategorie	Buitenluidsprekers
Ontwerp	2-driver, 2-way outdoor satellite, acoustic suspension, weather, water, UV-resistant PolyGlass™ enclosure
Impedantie	Compatible with 8 Ω
Wisselfilter	2nd-order electro-acoustic at 2.5 kHz
Frequentierespons op de as	±3 dB from 110 Hz - 20 kHz
Hogetonenunit	3/4" (1.9cm) X-PAL™ dome, ferro-fluid damped / cooled, Reduced Edge Diffraction (RED™) Technology, die-cast low diffraction baffle/heat sink
Middentonenunit	6" (16 cm) mineral-filled polypropylene cone, Nitrile-Butadiene Rubber (NBR) surround
Gevoeligheid (ruimte / anechoïsch)	92 dB / 88 dB

Technische specificaties

Onderste grensfrequentie	74 Hz
Aanbevolen versterkervermogen	15 - 120 W
Maximaal ingangsvermogen	80 W
Afmetingen (DIAMETER X DEPTH)	7” (diameter) x 10” (depth) 17.8cm x 25.4cm
Gewicht	5.7 lbs. (2.9 kg)
Afwerkingen	Satin Bronze