Paradigm Loudspeakers Premier 120B v2

Monitorluidsprekers



Technische specificaties

Merk	Paradigm Loudspeakers
Model	Premier 120B v2
Productcategorie	Monitorluidsprekers
Ontwerp	2-driver, 2-way ported bookshelf with AL-MAC, AL-MAG, OSW™, en PPA™
Impedantie	Compatible with 8 Ω
Wisselfilter	2nd Order Electro-acoustic at 1.2kHz (tweeter/midwoofer)
Frequentierespons op de as	±3dB from 62Hz - 23kHz
Frequentierespons 30° buiten de as	±3dB from 62Hz - 20kHz
Hogetonenunit	1” (25mm) AL-MAC™ Ceramic Dome with Oblate Spheroid Waveguide (OSW™) en Perforated Phase-Aligning (PPA™) Tweeter Lens, ferro-fluid damped / cooled

Technische specificaties

Midden-/lagetonenunit	5.5” (140mm) Ultra-High-Excursion AL-MAG™ Cone with Perforated Phase-Aligning (PPA™) Lens, Gen3 Active Ridge Technology (ART™) met Vertical Mounting System, en a 1” hightemp multi-layered voice coil with ventilated Apical™ former
Gevoeligheid (ruimte / anechoïsch)	90dB / 87dB
Onderste grensfrequentie	39 Hz (DIN)
Aanbevolen versterkervermogen	15 - 130 Ws
Maximaal ingangsvermogen	70 Ws
Afmetingen (H × B × D) (INCLUDES GRILLE).	12” x 7” x 12.1” (30.5 cm x 17.8 cm x 30.7 cm)
Gewicht	16.3 lbs (7.4 kg) each
Afwerkingen	Piano Zwart, Zwart Walnoot, Walnoot, Satin Wit