Paradigm Loudspeakers Rock Monitor 80-SM

Buitenluidsprekers



Technische specificaties

Merk	Paradigm Loudspeakers
Model	Rock Monitor 80-SM
Productcategorie	Buitenluidsprekers
Ontwerp	Single speaker system with stereo L/R inputs, 3-driver, 2 x 2-way coaxially mounted high-frequency drivers, weather, water, UV-resistant sealed enclosure, self draining fissures
Impedantie	Compatible with 4 Ω Mono; 8 Ω / channel Stereo Input
Afmetingen (H × B × D)	15.125" × 13.375" × 13" (38.4cm × 34.0cm × 33.0cm)
Wisselfilter	Twee 2nd-order electro-acoustic at 2.5 kHz
Frequentierespons op de as	±2 dB from 63 Hz - 20 kHz
Frequentierespons 30° buiten de as	±2 dB from 63 Hz - 18 kHz
Hogetonenunit	Twee 25-mm (1 in) PTD™ domes

Technische specificaties

Lagetonenunit	Dual voice-coil, 190-mm (7-1/2 in) ICP™ cone, die-cast chassis
Gevoeligheid (ruimte / anechoïsch)	90 dB (groundplane measurement) /
Onderste grensfrequentie	42 Hz (DIN)
Aanbevolen versterkervermogen	15 - 120 W Mono; 15 - 60 W / channel Stereo Input
Maximaal ingangsvermogen	80 W Mono; 40 W / channel Stereo Input
Gewicht	17 lbs. (7.7 kg)
Afwerkingen	Northeastern Dark Granite, Fieldstone